

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROTOSTAR UV FP 64-40602 Silver
Material number : 072484U20

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:
From outside US: : (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free) : 1-800-5355-053

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Irritant R36: Irritating to eyes.
Irritant R43: May cause sensitisation by skin contact.
Sensitising :

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

Dangerous for the environment

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazardous components which must be listed on the label:

48145-04-6	2-phenoxyethyl acrylate
162881-26-7	4,4'-Isopropylidenediphenol, ethoxylated, esters with acrylic acid and isononanoic acid
52408-84-1	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
	Glycerol, propoxylated, esters with acrylic acid

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

Chemical name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Bisphenol A ethoxylate diacrylate	64401-02-1 01-2119969511-34	Xi; R36	Eye Irrit. 2; H319	>= 25 - < 50
2-phenoxyethyl acrylate	48145-04-6 256-360-6 01-2119980532-35		Aquatic Chronic 2; H411 Skin Sens. 1A; H317	>= 20 - < 25
4,4'- Isopropylidenediph enol, ethoxylated, esters with acrylic acid and isononanoic acid	Not Assigned 919-846-5 01-2120087346-49	Xi; Xi; R43 N; N; R51/53	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 10 - < 20
aluminium powder (stabilised)	7429-90-5 231-072-3 01-2119529243-45	F; R11	Flam. Sol. 1; H228	>= 1 - < 10
acrylate	Not Assigned	Xi; Xi; R36	Eye Irrit. 2; H319	>= 3 - < 10
1-isopropyl-2,2- dimethyltrimethylen e diisobutyrate	6846-50-0 229-934-9 01-2119451093-47		Aquatic Chronic 3; H412	>= 2.5 - < 10
phenyl bis(2,4,6- trimethylbenzoyl)- phosphine oxide	162881-26-7 423-340-5 01-2119489401-38	R43 R53	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 2.5 - < 10
Glycerol, propoxylated, esters with acrylic acid	52408-84-1 500-114-5 01-2119487948-12	Xi; Xi; R36 Xi; R43	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 3

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious place in recovery position and seek medical

ROTOSTAR UV FP 64-40602 Silver

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
4.2	09.01.2017	102000000351	Date of first issue: 17.03.2014

- advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Dry sand
ABC powder
Foam
- Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

This information is not available.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-

ROTOSTAR UV FP 64-40602 Silver

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
4.2	09.01.2017	102000000351	Date of first issue: 17.03.2014

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis (Version Date)
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40 (2011-12-01)
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	4 mg/m ³	GB EH40 (2011-12-01)
Further information	The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Where no specific short-term exposure limit is listed, a figure three times the long-term			

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

	exposure should be used			
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40 (2005-04-06)
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
aluminium powder (stabilised)	7429-90-5	TWA (Respirable)	4 mg/m ³	GB EH40 (2005-04-06)
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
aluminium powder (stabilised)	7429-90-5	TWA (inhalable dust)	10 mg/m ³	GB EH40 (2011-12-01)
Further information	For the purposes of these limits, respirable dust and inhalable dust are those			

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

	<p>fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			
aluminium powder (stabilised)	7429-90-5	TWA (Respirable dust)	4 mg/m3	GB EH40 (2011-12-01)
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Bisphenol A ethoxylate diacrylate (64401-02-	Workers	Inhalation	long term – systemic effects	3.52 mg/m3

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

1)				
	Workers	Skin contact	long term – systemic effects	2 mg/kg
	Consumers	Inhalation	long term – systemic effects	0.87 mg/m ³
	Consumers	Skin contact	long term – systemic effects	1 mg/kg
	Consumers	Ingestion	long term – systemic effects	0.5 mg/kg
aluminium (7429-90-5)	Workers	Inhalation	long term – local effects	3.72 mg/m ³
	Consumers	Oral	long term – systemic effects	3.95 mg/kg
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0)	Workers	Skin contact	long term – systemic effects	31.20 mg/kg
	Workers	Inhalation	long term – systemic effects	110 mg/m ³
	Consumers	Ingestion	long term – systemic effects	18.8 mg/kg
	Consumers	Skin contact	long term – systemic effects	18.8 mg/kg
	Consumers	Inhalation	long term – systemic effects	32.60 mg/m ³
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide (162881-26-7)	Workers	Skin contact	short term – systemic effects acute	3.0 mg/kg
	Workers	Inhalation	short term – systemic effects acute	21 mg/m ³
	Workers	Skin contact	long term – systemic effects	3.0 mg/kg
	Workers	Inhalation	long term – systemic effects	21 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	5.2 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	1.5 mg/kg
	Consumers	Ingestion	Long-term systemic effects	1.5 mg/kg
hydroxycyclohexyl phenyl ketone (947-19-3)	Workers	Skin contact	short term – systemic effects	2.5 mg/kg

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

	Workers	Inhalation	short term – systemic effects	7 mg/m ³
	Workers	Skin contact	long term – systemic effects	2.5 mg/kg
	Workers	Inhalation	long term – systemic effects	7 mg/m ³
	Consumers	Ingestion	short term – systemic effects	1.25 mg/kg
	Consumers	Skin contact	short term – systemic effects	1.25 mg/kg
	Consumers	Inhalation	short term – systemic effects	1.7 mg/m ³
	Consumers	Ingestion	long term – systemic effects	1.25 mg/kg
	Consumers	Skin contact	long term – systemic effects	1.25 mg/kg
	Consumers	Inhalation	long term – systemic effects	1.7 mg/m ³
Glycerol, propoxylated, esters with acrylic acid (52408-84-1)	Workers	Skin contact	long term – systemic effects	1.92 mg/kg
	Workers	Inhalation	long term – systemic effects	16.22 mg/m ³
	Consumers	Ingestion	long term – systemic effects	1.39 mg/kg
	Consumers	Skin contact	long term – systemic effects	1.15 mg/kg
	Consumers	Inhalation	long term – systemic effects	4.87 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Bisphenol A ethoxylate diacrylate (64401-02-1)	Fresh water	0.006 mg/l
	Soil	0.1208 mg/kg
	Marine sediment	0.06216 mg/kg
	Fresh water sediment	0.6216 mg/kg
	STP	1.43 mg/l
	Marine water	0.0006 mg/l
aluminium (7429-90-5)	Fresh water	0.0749 mg/l
	clarification plant	20 mg/l
1-isopropyl-2,2-	Fresh water	0.014 mg/l

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

dimethyltrimethylene diisobutyrate (6846-50-0)		
	Marine water	0.0014 mg/l
	Fresh water sediment	5.29 mg/kg
	Soil	1.05 mg/kg
	STP	3 mg/l
	Marine sediment	0.529 mg/kg
hydroxycyclohexyl phenyl ketone (947-19-3)	Fresh water	0.0144 mg/l
Glycerol, propoxylated, esters with acrylic acid (52408-84-1)	Soil	0.00111 mg/kg
	Fresh water	0.00574 mg/l
	Fresh water sediment	0.01697 mg/kg
	Marine water	0.000574 mg/l
	Marine sediment	0.001697 mg/kg
	STP	10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

Remarks

: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : silver
Odour : characteristic
Odour Threshold : No data available
pH : No data available
Freezing point : No data available
Boiling point/boiling range : No data available
Flash point : > 100 °C

Evaporation rate : No data available
Flammability (solid, gas) : No data available
Auto-flammability : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Relative density : No data available
Density : No data available
Bulk density : No data available
Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : No data available
Ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available
Flow time : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.

No data available

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

7429-90-5:

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

6846-50-0:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402

162881-26-7:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

ROTOSTAR UV FP 64-40602 Silver

Version 4.2	Revision Date: 09.01.2017	SDS Number: 102000000351	Print Date: 20.11.2018 Date of first issue: 17.03.2014
----------------	------------------------------	-----------------------------	---

Remarks: May cause skin irritation and/or dermatitis.

Components:

6846-50-0:

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Components:

6846-50-0:

Species: Rabbit
Exposure time: 72 h
Method: OECD Test Guideline 405
Result: No eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Further information

Product:

Remarks: No data available

Components:

48145-04-6:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: No data available

Components:

48145-04-6:

Additional ecological information : Remarks: No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SECTION 14: Transport information

14.1 UN number

ADR : UN 3082

IMDG : UN 3082

IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(2-phenoxyethyl acrylate)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

ROTOSTAR UV FP 64-40602 Silver

Version 4.2 Revision Date: 09.01.2017 SDS Number: 102000000351 Print Date: 20.11.2018
Date of first issue: 17.03.2014

IATA (2-phenoxyethyl acrylate)
: Environmentally hazardous substance, liquid, n.o.s.
(2-phenoxyethyl acrylate)

14.3 Transport hazard class(es)

ADR : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADR
Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (E)

IMDG
Packing group : III
Labels : 9
EmS Number : F-A,S-F

IATA
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous Dangerous Goods

14.5 Environmental hazards

ADR
Environmentally hazardous : yes

IMDG
Marine pollutant : yes

14.6 Special precautions for user

Remarks : For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

ROTOSTAR UV FP 64-40602 Silver

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
4.2	09.01.2017	102000000351	Date of first issue: 17.03.2014

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of R-Phrases

R11 : Highly flammable.
R36 : Irritating to eyes.
R43 : May cause sensitisation by skin contact.
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53 : May cause long-term adverse effects in the aquatic environment.

Full text of H-Statements

H228 : Flammable solid.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Chronic aquatic toxicity
Eye Irrit. : Eye irritation
Flam. Sol. : Flammable solids
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -

ROTOSTAR UV FP 64-40602 Silver

Version	Revision Date:	SDS Number:	Print Date: 20.11.2018
4.2	09.01.2017	102000000351	Date of first issue: 17.03.2014

International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN