

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROTOSTAR UV FP 64-40601 Silver
Product code : 014117U20

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein

Telephone : +499152770

Telefax : +499152777008

E-mail address of person responsible for the SDS : msds.eckart@altana.com

1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:
From outside US : (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free) : 1-800-5355-053

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P201 Obtain special instructions before use. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Hazardous components which must be listed on the label:

Epoxy acrylate
Propylidynetrimethanol, ethoxylated, esters with acrylic acid
2-phenoxyethyl acrylate
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
2-Propenoic acid, ester with C12-16-alkyl glycidyl ether
Glycerol, propoxylated, esters with acrylic acid

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
Epoxy acrylate	55818-57-0 01-2119490020-53	Skin Sens. 1; H317	>= 25 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version
4.0

Revision Date:
11.11.2018

SDS Number:
102000000093

Print Date: 19.11.2018
Date of first issue: 21.01.2014

Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5 500-066-5 01-2119489900-30	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 20 - < 25
2-phenoxyethyl acrylate	48145-04-6 256-360-6 01-2119980532-35	Aquatic Chronic 2; H411 Skin Sens. 1A; H317	>= 10 - < 20
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 1 - < 10
acrylate	Not Assigned	Eye Irrit. 2; H319	>= 1 - < 10
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 3 - < 10
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7 423-340-5 015-189-00-5 01-2119489401-38	Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 2,5 - < 10
2-Propenoic acid, ester with C12-16-alkyl glycidyl ether	68071-40-9 01-2120755565-46-xxxx	Skin Sens. 1; H317	>= 1 - < 10
Glycerol, propoxylated, esters with acrylic acid	52408-84-1 500-114-5 01-2119487948-12	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move the victim to fresh air.
Do not leave the victim unattended.
- Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0	Revision Date: 11.11.2018	SDS Number: 102000000093	Print Date: 19.11.2018 Date of first issue: 21.01.2014
----------------	------------------------------	-----------------------------	---

Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
May cause an allergic skin reaction.
Suspected of damaging the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand
ABC powder
Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
4.0	11.11.2018	102000000093	Date of first issue: 21.01.2014

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Do not flush with water.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids.
Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium powder (stabilised)	7429-90-5	NGV (Total)	5 mg/m ³	SE AFS
Further information	Inhalable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version
4.0

Revision Date:
11.11.2018

SDS Number:
102000000093

Print Date: 19.11.2018
Date of first issue: 21.01.2014

	also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method.		
	NGV (Respirable)	2 mg/m ³	SE AFS
Further information	Inhalable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.3 and having sampling characteristics as specified in paragraph 5.1. Respirable dust refers to the dust fraction as defined in the Swedish Standard SS-EN 481, Workplace Atmospheres - Size fraction definitions for measurement of airborne particles, 1st ED., 1993., Section 2.11 and having sampling characteristics as specified in paragraph 5.3. Total dust refers to all the particles (aerosols) trapped in a filter in the sampling apparatus described in Methods, Sampling of total dust and respirable dust, method nr 1010, published by the National Board of Occupational Safety and Health, now Work Environment Authority. The filter diameter shall normally be 37 mm but can also be 25 mm. Despite its name, not the total amount of airborne particles is measured by this method.		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Epoxy acrylate	Workers	Skin contact	long term – systemic effects	33 mg/kg
	Workers	Inhalation	long term – systemic effects	1,17 mg/m ³
	Consumers	Inhalation	long term – systemic effects	0,29 mg/m ³
	Consumers	Skin contact	long term – systemic effects	16,67 mg/kg
	Consumers	Oral	long term – systemic effects	0,17 mg/kg
	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Workers	Skin contact	long term – systemic effects
Workers		Inhalation	long term – systemic effects	16,2 mg/m ³
Consumers		Skin contact	long term – systemic effects	0,5 mg/kg
Consumers		Inhalation	long term – systemic effects	4,9 mg/m ³
Consumers		Ingestion	long term – systemic effects	1,4 mg/kg
aluminium powder (stabilised)		Workers	Inhalation	long term – local effects
	Consumers	Oral	long term – systemic effects	3,95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3,72 mg/m ³
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Workers	Skin contact	long term – systemic effects	31,20 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version
4.0

Revision Date:
11.11.2018

SDS Number:
102000000093

Print Date: 19.11.2018
Date of first issue: 21.01.2014

	Workers	Inhalation	long term – systemic effects	110 mg/m ³
	Consumers	Ingestion	long term – systemic effects	18,8 mg/kg
	Consumers	Skin contact	long term – systemic effects	18,8 mg/kg
	Consumers	Inhalation	long term – systemic effects	32,60 mg/m ³
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Workers	Skin contact	short term – systemic effects acute	3,0 mg/kg
	Workers	Inhalation	short term – systemic effects acute	21 mg/m ³
	Workers	Skin contact	long term – systemic effects	3,0 mg/kg
	Workers	Inhalation	long term – systemic effects	21 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	5,2 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	1,5 mg/kg
	Consumers	Ingestion	Long-term systemic effects	1,5 mg/kg
Glycerol, propoxylated, esters with acrylic acid	Workers	Skin contact	long term – systemic effects	1,92 mg/kg
	Workers	Inhalation	long term – systemic effects	16,22 mg/m ³
	Consumers	Ingestion	long term – systemic effects	1,39 mg/kg
	Consumers	Skin contact	long term – systemic effects	1,15 mg/kg
	Consumers	Inhalation	long term – systemic effects	4,87 mg/m ³
hydroxycyclohexyl phenyl ketone	Workers	Skin contact	short term – systemic effects	2,5 mg/kg
	Workers	Inhalation	short term – systemic effects	7 mg/m ³
	Workers	Skin contact	long term – systemic effects	2,5 mg/kg
	Workers	Inhalation	long term – systemic effects	7 mg/m ³
	Consumers	Ingestion	short term – systemic effects	1,25 mg/kg
	Consumers	Skin contact	short term – systemic effects	1,25 mg/kg
	Consumers	Inhalation	short term – systemic effects	1,7 mg/m ³
	Consumers	Ingestion	long term – systemic effects	1,25 mg/kg
	Consumers	Skin contact	long term – systemic effects	1,25 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version
4.0

Revision Date:
11.11.2018

SDS Number:
102000000093

Print Date: 19.11.2018
Date of first issue: 21.01.2014

	Consumers	Inhalation	long term – systemic effects	1,7 mg/m3
--	-----------	------------	------------------------------	-----------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Epoxy acrylate	Fresh water	0,1 mg/l
	Marine water	0,01 mg/l
	Fresh water sediment	35,8 mg/kg
	Marine sediment	3,58 mg/kg
	clarification plant	10 mg/l
	Soil	7,1 mg/kg
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Soil	0,00587 mg/kg
	Fresh water	0,00195 mg/l
	Fresh water sediment	0,0082 mg/kg
	STP	10 mg/l
	Marine water	0,000195 mg/l
	Marine sediment	0,00082 mg/kg
aluminium powder (stabilised)	Fresh water	0,0749 mg/l
	clarification plant	20 mg/l
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Fresh water	0,014 mg/l
	Marine water	0,0014 mg/l
	Fresh water sediment	5,29 mg/kg
	Soil	1,05 mg/kg
	STP	3 mg/l
	Marine sediment	0,529 mg/kg
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Fresh water	1 µg/l
	Marine water	1 µg/l
	STP	1 mg/l
	Fresh water sediment	0,712 mg/kg
	Marine sediment	0,712 mg/kg
	Soil	20 mg/kg
Glycerol, propoxylated, esters with acrylic acid	Soil	0,00111 mg/kg
	Fresh water	0,00574 mg/l
	Fresh water sediment	0,01697 mg/kg
	Marine water	0,000574 mg/l
	Marine sediment	0,001697 mg/kg
	STP	10 mg/l
hydroxycyclohexyl phenyl ketone	Fresh water	0,0144 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Goggles

Safety glasses

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

- Hand protection
Material : Solvent-resistant gloves (butyl-rubber)
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use suitable breathing protection if workplace concentration requires.
- Environmental exposure controls**
- Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : No data available
- Odour : characteristic
- Odour Threshold : No data available
- pH : No data available
- Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 100 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Auto-ignition temperature : No data available

Smoldering temperature : No data available

Decomposition temperature : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Bulk density : No data available

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Flow time : No data available

9.2 Other information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
4.0	11.11.2018	102000000093	Date of first issue: 21.01.2014

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.
Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Do not allow evaporation to dryness.
No data available

10.5 Incompatible materials

Materials to avoid : Acids
Bases
Oxidizing agents

10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.
Thermal decomposition : This information is not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

:

Result: Skin irritation

Remarks: May cause skin irritation and/or dermatitis.

:

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: No skin irritation

:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species: Rabbit
Exposure time: 72 h
Method: OECD Test Guideline 405
Result: No eye irritation

Glycerol, propoxylated, esters with acrylic acid:

Remarks: Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version
4.0

Revision Date:
11.11.2018

SDS Number:
102000000093

Print Date: 19.11.2018
Date of first issue: 21.01.2014

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

Components:

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Result: May cause sensitisation by skin contact.

Remarks: Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

2-Propenoic acid, ester with C12-16-alkyl glycidyl ether:

Result: May cause sensitisation by skin contact.

Glycerol, propoxylated, esters with acrylic acid:

Remarks: Causes sensitisation.

May cause sensitisation of susceptible persons by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

Components:

Propylidyntrimethanol, ethoxylated, esters with acrylic acid:

Remarks: No data available

2-phenoxyethyl acrylate:

Remarks: No data available

Glycerol, propoxylated, esters with acrylic acid:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Propylidyntrimethanol, ethoxylated, esters with acrylic acid:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 10.232,73 mg/l

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 2,46 mg/l

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Components:

Propylidyntrimethanol, ethoxylated, esters with acrylic acid:

Additional ecological information : No data available

2-phenoxyethyl acrylate:

Additional ecological information : No data available

Glycerol, propoxylated, esters with acrylic acid:

Additional ecological information : No data available

SECTION 13: Disposal considerations

European Waste Catalogue : 08 03 12 - waste ink containing dangerous substances

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
In accordance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version 4.0 Revision Date: 11.11.2018 SDS Number: 102000000093 Print Date: 19.11.2018
Date of first issue: 21.01.2014

SECTION 14: Transport information

14.1 UN number

14.2 UN proper shipping name

14.3 Transport hazard class(es)

14.4 Packing group

14.5 Environmental hazards

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H361d : Suspected of damaging the unborn child.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Irrit. : Eye irritation
Flam. Sol. : Flammable solids
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
SE AFS : Sweden. Occupational Exposure Limit Values

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



ROTOSTAR UV FP 64-40601 Silver

Version	Revision Date:	SDS Number:	Print Date: 19.11.2018
4.0	11.11.2018	102000000093	Date of first issue: 21.01.2014

SE AFS / NGV : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SE / EN