

**STAPA UV CHROMAL X/H Aluminium Paste**

Version 1.0      Revision Date: 03/21/2018      SDS Number: 102000000295      Date of last issue: -  
Date of first issue: 03/21/2018

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : STAPA UV CHROMAL X/H Aluminium Paste  
Product code : 055223G60

**Manufacturer or supplier's details**

Company name of supplier : ECKART GmbH  
Address : Guentersthal 4  
Hartenstein 91235  
Telephone : +499152770  
Telefax : +499152777008  
Emergency telephone number : CHEMTREC: 800-424-9300  
CHEMTREC: 1-703-527-3387 (International)

GBK Gefahrgut Buero GmbH, Ingelheim, Germany:  
From outside US: (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free):1-800-5355-053

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Acute aquatic toxicity : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H400 Very toxic to aquatic life.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.

## STAPA UV CHROMAL X/H Aluminium Paste

Version 1.0      Revision Date: 03/21/2018      SDS Number: 102000000295      Date of last issue: -  
Date of first issue: 03/21/2018

---

**Response:**

P391      Collect spillage.

**Disposal:**

P501      Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Alcohols, C11-14-iso-, C13-rich

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum	7429-90-5	>= 50 -< 70
Octadecanoic acid	57-11-4	>= 1 -< 5
Octadecanoic acid	57-11-4	>= 1 -< 5

---

**SECTION 4. FIRST AID MEASURES**

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.  
No hazards which require special first aid measures.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
  
Flush eyes with water as a precaution.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.

## STAPA UV CHROMAL X/H Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : None known.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry sand  
Special powder against metal fire
- Unsuitable extinguishing media : Water  
Foam  
ABC powder  
Carbon dioxide (CO<sub>2</sub>)
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Use personal protective equipment.
- Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Remove all sources of ignition.  
Avoid dust formation.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## STAPA UV CHROMAL X/H Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

Methods and materials for containment and cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Do not flush with water.  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.  
Earthing of containers and apparatuses is essential.

Normal measures for preventive fire protection.

Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.

For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.

Hygiene measures : Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep containers tightly closed in a cool, well-ventilated place.  
Keep container closed when not in use.  
Keep away from sources of ignition - No smoking.

Keep container tightly closed in a dry and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store together with oxidizing and self-igniting products.  
Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Further information on storage stability : No decomposition if stored and applied as directed.

## STAPA UV CHROMAL X/H Aluminium Paste

Version 1.0      Revision Date: 03/21/2018      SDS Number: 102000000295      Date of last issue: -  
 Date of first issue: 03/21/2018

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum	7429-90-5	LMPE-PPT	10 mg/m <sup>3</sup>	MX OEL
		LMPE-PPT (Dust)	10 mg/m <sup>3</sup>	MX OEL
		TWA (Respirable fraction)	1 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	1 mg/m <sup>3</sup> (Aluminium)	ACGIH
Octadecanoic acid	57-11-4	TWA	10 mg/m <sup>3</sup>	ACGIH
Octadecanoic acid	57-11-4	TWA	10 mg/m <sup>3</sup>	ACGIH

#### Personal protective equipment

Respiratory protection : Use suitable breathing protection if workplace concentration requires.

Hand protection  
 Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace

## STAPA UV CHROMAL X/H Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Long sleeved clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 120 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: The product is not flammable.
Auto-flammability	: not auto-flammable
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Solubility(ies)	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Explosive properties	: Not explosive

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

**STAPA UV CHROMAL X/H Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapour/air-mixtures are explosive at intense warming. Stable under recommended storage conditions.

Conditions to avoid : Do not allow to dry.  
No data available

Incompatible materials : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STAPA UV CHROMAL X/H Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

In accordance with local and national regulations.

Contaminated packaging :

Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

In accordance with local and national regulations.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.



## STAPA UV CHROMAL X/H Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

	(C13-C16 Isoalcohols)
Class	: 9
Packing group	: III
Labels	: Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft)	: 956
Packing instruction (passenger aircraft)	: 956
<b>IMDG-Code</b>	
UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(C13-C16 Isoalcohols)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes
Remarks	: For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### NOM-002-SCT

Not regulated as a dangerous good

### Special precautions for user

Remarks	: For single packagings <=5L / 5 kg, or combination packagings containing inner packagings <= 5L / 5 kg net per inner packaging, SV375 ADR, 2.10.2.7 IMDG-Code, A197 IATA-DGR may be applied.
---------	---

---

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Federal Law for the control of chemical precursors, essential chemical products and machinery for producing capsules, tablets and pills. : Not applicable

## STAPA UV CHROMAL X/H Aluminium Paste

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 MX OEL : Mexico. Occupational Exposure Limits  
 ACGIH / TWA : 8-hour, time-weighted average  
 MX OEL / LMPE-PPT : Time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 03/21/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

**STAPA UV CHROMAL X/H Aluminium Paste**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/21/2018	102000000295	Date of first issue: 03/21/2018

---

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MX / EN