

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version 3.1      Revision Date: 04.01.2019      SDS Number: 102000024231      Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : PlatinVario AE-82005  
Product code : 022156JD0

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH  
Guentersthal 4  
91235 Hartenstein  
  
Telephone : +499152770  
  
Telefax : +499152777008  
  
E-mail address of person responsible for the SDS : msds.eckart@altana.com

#### 1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:  
From outside US : (001) 352-323-3500  
(First call in English, response in your language is possible)  
US & Canada (toll free) : 1-800-5355-053

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable solids, Category 1      H228: Flammable solid.  
  
Eye irritation, Category 2      H319: Causes serious eye irritation.  
  
Specific target organ toxicity - single exposure, Category 3, Central nervous system      H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version 3.1      Revision Date: 04.01.2019      SDS Number: 102000024231      Print Date: 07.01.2019  
Date of first issue: 13.12.2016

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H228 H319 H336	Flammable solid. Causes serious eye irritation. May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210  P261  P280  <b>Response:</b> P304 + P340 + P312  P370 + P378  P370 + P378	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. In case of fire: Use for extinction: Special powder for metal fires. In case of fire: Use for extinction: Dry sand.

Hazardous components which must be listed on the label:

ethyl acetate  
propan-2-ol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification REGULATION (EC) No 1272/2008	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 607-022-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 25 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

propan-2-ol	67-63-0 200-661-7 603-117-00-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 25 - < 50
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 20 - < 25

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move the victim to fresh air.  
Do not leave the victim unattended.
- Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water.
- If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
- Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version 3.1      Revision Date: 04.01.2019      SDS Number: 102000024231      Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Dry sand  
Special powder against metal fire

Unsuitable extinguishing media : Water  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
ABC powder

#### 5.2 Special hazards arising from the substance or mixture

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Use personal protective equipment.  
Avoid dust formation.  
Remove all sources of ignition.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Use mechanical handling equipment.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Do not flush with water.  
Keep in suitable, closed containers for disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version	Revision Date:	SDS Number:	Print Date: 07.01.2019
3.1	04.01.2019	102000024231	Date of first issue: 13.12.2016

---

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Keep away from heat and sources of ignition.  
Avoid dust formation.  
Ensure adequate ventilation.
- Avoid formation of respirable particles.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Earthing of containers and apparatuses is essential. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.
- Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Keep away from sources of ignition - No smoking.
- No smoking. Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Protect from humidity and water. Do not allow to dry.
- Advice on common storage : Do not store together with oxidizing and self-igniting products. Never allow product to get in contact with water during storage.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Further information on storage stability : No decomposition if stored and applied as directed.
-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

### 7.3 Specific end use(s)

This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethyl acetate	141-78-6	TWA	200 ppm 730 mg/m <sup>3</sup>	CH SUVA
Further information	National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	400 ppm 1.460 mg/m <sup>3</sup>	CH SUVA
Further information	National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
Further information	Indicative			
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
Further information	Indicative			
propan-2-ol	67-63-0	TWA	200 ppm 500 mg/m <sup>3</sup>	CH SUVA
Further information	National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	400 ppm 1.000 mg/m <sup>3</sup>	CH SUVA
Further information	National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
aluminium powder (stabilised)	7429-90-5	TWA (alveolate dust)	3 mg/m <sup>3</sup>	CH SUVA
		TWA (inhalable dust)	10 mg/m <sup>3</sup>	CH SUVA
		TWA (alveolate dust)	3 mg/m <sup>3</sup>	CH SUVA
Further information	National Institute for Occupational Safety and Health, See Annex 1.8.2: Inert dusts, general dust value Inert dusts are dusts that, up to present knowledge, are not resorbed, nor lead to fibrogenic action in the lungs and that do not provoke disease symptoms. Because inert dusts can lead to			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

	mechanical irritation of the respiratory system, a limit value of 3 mg/m <sup>3</sup> (alveolate dust), measured according to EN 481, and 10 mg/m <sup>3</sup> for inhalable dust applies. The limit value for inert dust only applies if no addition occurs of harmful substances like asbest, quarz etc. As inert dusts are known, e.g.: Aluminium oxide (Alundum and Corundum), Calcium carbonate (Chalk), Calcium sulphate (Gypsum), Magnesium carbonate (Magnesite), Silicium carbide (Carborundum), Starch, Titanium dioxide, Cellulose, Tin dioxide. The concentration of not inert dusts in the respiratory air, for which no limit value has been established yet, should never exceed the concentration of the inert dust.		
	TWA (alveolate dust)	3 mg/m <sup>3</sup> (Aluminium)	CH SUVA
Further information	Inert dusts, general dust limit value; dusts are, according to present knowledge, being regarded as inert, when they are not resorbed and do not provoke an increased generation of connective tissue (fibrogenic action) and which do not provoke specific symptoms. As such dusts can influence the function of the airways by mechanical irritation, a limit value of 3 mg/m <sup>3</sup> applies for respirable dust, measured according to EN 481, and a limit value of 10 mg/m <sup>3</sup> for inhalable dust., National Institute for Occupational Safety and Health, See Annex 1.8.2: Inert dusts, general dust value Inert dusts are dusts that, up to present knowledge, are not resorbed, nor lead to fibrogenic action in the lungs and that do not provoke disease symptoms. Because inert dusts can lead to mechanical irritation of the respiratory system, a limit value of 3 mg/m <sup>3</sup> (alveolate dust), measured according to EN 481, and 10 mg/m <sup>3</sup> for inhalable dust applies. The limit value for inert dust only applies if no addition occurs of harmful substances like asbest, quarz etc. As inert dusts are known, e.g.: Aluminium oxide (Alundum and Corundum), Calcium carbonate (Chalk), Calcium sulphate (Gypsum), Magnesium carbonate (Magnesite), Silicium carbide (Carborundum), Starch, Titanium dioxide, Cellulose, Tin dioxide. The concentration of not inert dusts in the respiratory air, for which no limit value has been established yet, should never exceed the concentration of the inert dust.		

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
propan-2-ol	67-63-0	Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	CH BAT
		Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	CH BAT
		Acetone: 0.4 Millimoles per liter (Urine)	Immediately after exposure or after working hours	CH BAT
		Acetone: 0.4 Millimoles per liter (Blood)	Immediately after exposure or after working hours	CH BAT
aluminium powder (stabilised)	7429-90-5	Aluminium (Aluminium): 60 µg/g creatinine (Urine)	No time limit	CH BAT
		Aluminium	No time limit	CH BAT

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

		(Aluminium): 0.251 micromoles per millimole creatinine (Urine)	
--	--	--	--

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Workers	Inhalation	short term – local effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	short term – systemic effects	1468 mg/m <sup>3</sup>
	Workers	Inhalation	long term – local effects	734 mg/m <sup>3</sup>
	Workers	Skin contact	long term – systemic effects	63 mg/kg
	Workers	Inhalation	long term – systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	short term – local effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	short term – systemic effects	734 mg/m <sup>3</sup>
	Consumers	Inhalation	long term – local effects	367 mg/m <sup>3</sup>
	Consumers	Skin contact	long term – systemic effects	37 mg/kg
	Consumers	Inhalation	long term – systemic effects	367 mg/m <sup>3</sup>
	Consumers	Ingestion	long term – systemic effects	4,5 mg/kg
propan-2-ol	Workers	Skin contact	long term – systemic effects	888 mg/kg
	Workers	Inhalation	long term – systemic effects	500 mg/m <sup>3</sup>
	Consumers	Ingestion	long term – systemic effects	26 mg/kg
	Consumers	Skin contact	long term – systemic effects	319 mg/kg
	Consumers	Inhalation	long term – systemic effects	89 mg/m <sup>3</sup>
aluminium powder (stabilised)	Workers	Inhalation	long term – local effects	3,72 mg/m <sup>3</sup>
	Consumers	Oral	long term – systemic effects	3,95 mg/kg
	Workers	Inhalation	Long-term systemic effects	3,72 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Soil	0,148 mg/kg
	STP	650 mg/l
	Fresh water	0,24 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

	Marine water	0,024 mg/l
	Fresh water sediment	1,15 mg/kg
	Marine sediment	0,115 mg/kg
propan-2-ol	Soil	28 mg/kg
	Fresh water	140,9 mg/l
	Fresh water sediment	552 mg/kg
	Marine water	140,9 mg/l
	Marine sediment	552 mg/kg
	STP	2251 mg/l
aluminium powder (stabilised)	Fresh water	0,0749 mg/l
	clarification plant	20 mg/l

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection  
Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The exact break through time can be obtained from the protective glove producer and this has to be observed. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Recommended preventive skin protection Skin should be washed after contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Long sleeved clothing  
Safety shoes  
  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use suitable breathing protection if workplace concentration requires.  
  
In the case of dust or aerosol formation use respirator with an approved filter.

#### Environmental exposure controls

Water : The product should not be allowed to enter drains, water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version	Revision Date:	SDS Number:	Print Date: 07.01.2019
3.1	04.01.2019	102000024231	Date of first issue: 13.12.2016

---

courses or the soil.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: Pasty solid
Colour	: silver
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Freezing point	: No data available
Boiling point/boiling range	: 76 °C
Flash point	: -4 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: The substance or mixture is a flammable solid with the category 1.
Self-ignition	: not auto-flammable not auto-flammable
Auto-ignition temperature	: No data available
Smoldering temperature	: No data available
Decomposition temperature	: No data available
Explosive properties	: Not explosive Vapours may form explosive mixture with air. Not explosive Vapours may form explosive mixture with air.
Oxidizing properties	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version	Revision Date:	SDS Number:	Print Date: 07.01.2019
3.1	04.01.2019	102000024231	Date of first issue: 13.12.2016

---

Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Bulk density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	: Reacts with alkalis, acids, halogenes and oxidizing agents. Contact with acids and alkalis may release hydrogen. Mixture reacts slowly with water resulting in evolution of hydrogen. Vapours may form explosive mixture with air.
	Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid	: Do not allow to dry.
---------------------	------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version 3.1      Revision Date: 04.01.2019      SDS Number: 102000024231      Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Acids  
Bases  
Oxidizing agents  
Highly halogenated compounds

### 10.6 Hazardous decomposition products

Contact with water or humid air : This information is not available.

Thermal decomposition : This information is not available.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

##### ethyl acetate:

Acute oral toxicity : (Rat): 5.620 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 56 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 (Rabbit): > 18.000 mg/kg

##### propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

##### aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

### **Product:**

Remarks: May cause skin irritation in susceptible persons.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Product:**

Remarks: Eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

#### **ethyl acetate:**

Toxicity to daphnia and other aquatic invertebrates : (Daphnia (water flea)): 717 mg/l

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version 3.1      Revision Date: 04.01.2019      SDS Number: 102000024231      Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

European Waste Catalogue : 12 01 04 - non-ferrous metal dust and particles  
European Waste Catalogue : 100321 - other particulates and dust (including ball-mill dust) containing dangerous substances

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.  
In accordance with local and national regulations.

---

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1325

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version  
3.1

Revision Date:  
04.01.2019

SDS Number:  
102000024231

Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

**IMDG** : UN 1325

**IATA** : UN 1325

### 14.2 UN proper shipping name

**ADR** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**IMDG** : FLAMMABLE SOLID, ORGANIC, N.O.S.  
(Aluminium pigment paste)

**IATA** : Flammable solid, organic, n.o.s.  
(Aluminium pigment paste)

### 14.3 Transport hazard class(es)

**ADR** : 4.1

**IMDG** : 4.1

**IATA** : 4.1

### 14.4 Packing group

#### **ADR**

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 40  
Labels : 4.1  
Tunnel restriction code : (E)

#### **IMDG**

Packing group : II  
Labels : 4.1  
EmS Code : F-A, S-G  
Remarks : IMDG Code segregation group 15 - Powdered metals

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 448  
Packing instruction (LQ) : Y441  
Packing group : II  
Labels : Flammable Solid

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 445  
Packing instruction (LQ) : Y441  
Packing group : II  
Labels : Flammable Solid

### 14.5 Environmental hazards

#### **ADR**

Environmentally hazardous : no

#### **IMDG**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version 3.1      Revision Date: 04.01.2019      SDS Number: 102000024231      Print Date: 07.01.2019  
Date of first issue: 13.12.2016

---

Marine pollutant : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 76,3 %

### 15.2 Chemical safety assessment

---

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H228 : Flammable solid.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.

### Full text of other abbreviations

Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Flam. Sol. : Flammable solids  
STOT SE : Specific target organ toxicity - single exposure  
2017/164/EU : Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU  
CH BAT : Switzerland. List of BAT-values  
CH SUVA : Switzerland. Limit values at the work place  
2017/164/EU / STEL : Short term exposure limit

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## PlatinVario AE-82005

Version	Revision Date:	SDS Number:	Print Date: 07.01.2019
3.1	04.01.2019	102000024231	Date of first issue: 13.12.2016

---

2017/164/EU / TWA : Limit Value - eight hours  
CH SUVA / TWA : Time Weighted Average  
CH SUVA / STEL : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN